

FICHE RELEVÉ OSMOZ

(CONFORMITÉ EN 81-70)

RENSEIGNEMENTS GÉNÉRAUX

CLIENT :	CHANTIER / RÉFÉRENCE :		
N° COMMANDE / N° DEVIS :	DÉLAI DÉPART :		
Charge utile :	kg	Vitesse nominale :	m/s
Tension réseau :	V	Relevé effectué le :	
Par :	Contact client :	Commercial OCTÉ :	

INFORMATIONS INSTALLATION EXISTANTE

Nb de niveaux :	(20 maximum)	ATTENTION : Au delà du 10 niveaux, rajouter une carte entrée sortie		
Entre niveau min. :	m	 COPTER OBLIGATOIRE Capteur optronique de sécurité avec bande crantée - si vitesse nominale (m/s) x 1,3 > entre-niveau min. (m) / 2 - si fort trafic (Hotel, Hopital, Bureau, ERP) - hydraulique		
Hauteur Dernier Niv.:	m			
Hauteur de gaine :	m			
Profondeur cuvette :	m			
Distance Armoire - Gaine :	m			
Simplex	Multiplex	Machinerie Haute	Machinerie Basse	

Armoire de manoeuvre

OCTÉ/SIMINOR SM 210 SC 640 Mod 7 SC 640 Mod 10 Pilote V1 OLEODYNE LIFT LIGHT OLEO OLEOMATE	AUTINOR A 50 A 150 A 190 A 200 SERIE A191/A32 SERIE ALPHA H 191	SCHINDLER MICONIC C MICONIC E MICONIC LX MICONIC EF KA ELCONIC SODIMAS NG 12 NG 120	KONE EPB2 NOVA OLEO TMS 516 OTIS NE / MS 300 AN4	THYSSENKRUPP/ MGTI/SORETEX MICRO 2000 TURBO 3000 OPTIMA 4000 SERIE C S200 SPRINTE ASP116E2	MAC PUARSA MICRO basic JOUGLET Armoire à relais OLEO MEA NG 01 ASCEL EUROPA
---	---	---	--	---	--

AUTRE (Marque et Type) Fournir impérativement le schéma de l'armoire

Motorisation Consommation du moteur de traction < 35A

2 vitesses

1 vitesse VF Asynchrone Boucle Ouverte : Fréquence Hz Fréquence minimum pour bon fonctionnement : 20 Hz

Hydraulique --> COPTER obligatoire

Manoeuvre

Blocage	Blocage / Enregistré	Collective Descente	Collective Complète RC*	Collective Complète*
			*Doublé le nombre de carte entrée sortie	

Commande et signalisation

Flèches de direction	Flèches de prochain départ
Maximum 24 VCC	

OPTIONS DEMANDÉES

Cabine Oui Non Boîte à boutons complète conservée Afficheur Synthèse vocale Téléalarme Pèse charge Bloc de secours Sirène	Palier Oui Non Boîte à boutons palière complète Fourniture Faisceaux boîte à boutons palières Indicateur à tous les niveaux Fourniture faisceaux indicateurs
---	---

OSMOZ INQUIRY FORM

(COMPLIANCE WITH EN 81-70)

GENERAL INFORMATION

CUSTOMER:		CUSTOMER / REFERENCE:	
N° ORDER / N° QUOTATION:		N° DEVICE:	
Duty load:	kg	Rated speed:	m/s
System voltage:	v	Date of the reading:	
by:	Contact customer:	OCTÉ Salesman:	

INSTALLATION INFORMATIONS

Nbr of level:	(maximum 20)	WARNING: Over 10 levels, add an input output card			
Between level min.:	m	 COPTER MANDATORY Optronique security sensor with perforated strip - if rated speed (m/s) x 1,3 > between level min. (m) / 2 - if high traffic (Hotel, Hospital, Office, ERP) - hydraulic			
Height Last Level:	m				
Shaft height:	m				
Pit depth:	m				
Controller - shaft distance:	m				
Simplex Multiplex Machine room: Above Below					
Controller					
OCTÉ/SIMINOR SM 210 SC 640 Mod 7 SC 640 Mod 10 Pilote V1 OLEODYNE LIFT LIGHT OLEO OLEOMATE	AUTINOR A 50 A 150 A 190 A 200 SERIE A191/A32 SERIE ALPHA H 191	SCHINDLER MICONIC C MICONIC E MICONIC LX MICONIC EF KA ELCONIC SODIMAS NG 12 NG 120	KONE EPB2 NOVA OLEO TMS 516 OTIS NE / MS 300 AN4	THYSSENKRUPP/ MGTI/SORETEX MICRO 2000 TURBO 3000 OPTIMA 4000 SERIE C S200 SPRINT ASP116E2	MAC PUARSA MICRO basic JOUGLET Armoire à relais OLEO MEA NG 01 ASCEL EUROPA
OTHER (Brands and Type) <u>Provide imperatively diagram of controller</u>					
Drive system <u>consumption of the traction motor < 35A</u>					
2 Speeds					
1 Speed	Asynchronous Frequency inverter Open Loop: Frequency		Hz	Minimum frequency for good operation: 20 Hz	
Hydraulic --> COPTER mandatory					
Controller					
Automatic push button	Non-directional collective	Down Collective	Full Collective RC*	Full Collective*	
*Double the number of input output card					
Command and signaling		Direction arrows Maximum 24 VCC	Next start arrows		

REQUESTED OPTIONS

Car Yes No Preserved complet operating panel Display Vocal synthesis Telealarme Overload weighting Emergency light Siren	Landing Yes No Complet landing panels Harnesses supply completed landing panels Indicator at all levels Harnesses supply indicators
---	---